

GAS Pressure WASHERS



Design Features

Our Engines

Honda powered engines ensure a long easy start life for each pressure washer. Each engine is tested twice before delivery. First time without pump and final test run includes load test so RPM can be adjusted to exact optimal performance.



Our Pumps

The finest quality featuring: brass manifolds, ceramic plungers (industrial models), soap injectors and thermal relief valves. Every pump is load tested for 9 minutes in our test facility. During this test the pressure is adjusted and a 17 point inspection is administered to ensure dependable operation before delivery.



Design

Our Frames

Designed for durability and portability, each frame design has years of research and field testing behind it. Pneumatic wheels, removable handles and pre-drilled reel mounting plates allow for everyday contractor usage. Each frame is sand blasted and powder coated to ensure long durable colour finish.



GAS PRESSURE WASHERS

Design Features

Our Promise

To manufacture quality products at a competitive price that you will be proud to own. Our brand name is on the line every time you squeeze the trigger.

Features



Warranty

All Gas Pressure Washers carry the following warranties:

Frames	Lifetime
Motors	2 Years
Pumps – Light Industrial Excluding wear items	2 Years
Pumps – Industrial Excluding wear items	5 Years
Accessories Including hose reels, hose, gun, wand, tips, injector, couplers, unloaders wheels	90 Days

Note: Wear items consist of:

Packing Kits, Oil Seal Kits, Valve Kits, O-Rings and Rubber Parts, Oil

2000 PSI, 2.5 GPM

- 🔥 Honda 5.0 HP GC Series OHC engine
- 🔥 Giant axial drive pump
- 🔥 Moving parts operate in an oil bath
- 🔥 Forged brass manifold with adjustable pressure
- 🔥 Maximum pump operating temperature of 27° C / 80° F
- 🔥 Chemical injector with soap metering valve
- 🔥 Thermal relief valve
- 🔥 Powder coated frame with removable handle
- 🔥 10 inch pneumatic wheels
- 🔥 36 inch gun and wand assembly
- 🔥 Blue non-marking hose with QD fittings
- 🔥 Nozzle orifice size – 3.5
- 🔥 4 Quick coupled nozzles:
15° (yellow), 25° (green), 40° (white) and
50° (black soap tip)
- 🔥 Pump Warranty: 2 Year Limited
(Excluding Wear Items)
- 🔥 Engine Warranty: 2 Years

HG202B



▼ HG202B

Giant Pump - 2000 PSI, 2.5 GPM, Single handle
"B" frame, 25 foot hose

Specifications

Power	Honda
Horsepower (HP / kW)	5.0 / 3.7
Fuel Capacity (US Gal / L)	.5 / 2.0
Pump	Giant Axial
Operating Pressure (PSI / Bar)	2000 / 138
Volume (US GPM / Litres)	2.5 / 9.5
Pressure Hose (Ft. / m)	25 / 7
Dimensions (in / cm)	34 x 21 x 33 / 82 x 51 x 80
Net Weight (lb. / kg)	55 / 25



GAS PRESSURE WASHERS

Light Industrial

2700 PSI, 2.5 GPM

- 🔥 Honda 6.0 HP GC Series OHC engine
- 🔥 Giant axial drive pump
- 🔥 Moving parts operate in an oil bath
- 🔥 Forged brass manifold with adjustable pressure
- 🔥 Maximum pump operating temperature of 27° C / 80° F
- 🔥 Chemical injector with soap metering valve
- 🔥 Thermal relief valve
- 🔥 Powder coated frame with removable handle
- 🔥 10 inch pneumatic wheels
- 🔥 36 inch gun and wand assembly
- 🔥 Blue non-marking hose with QD fittings
- 🔥 Nozzle orifice size – 3.5
- 🔥 4 Quick coupled nozzles:
15° (yellow), 25° (green), 40° (white) and 50° (black soap tip)
- 🔥 Pump Warranty: 2 Year Limited
(Excluding Wear Items)
- 🔥 Engine Warranty: 2 Years

HG272EH5



▼ HG272EH5

Giant Pump - 2700 PSI, 2.5 GPM, Two handle "E" frame,
Hose reel with 50 foot hose

Specifications

Power	Honda
Horsepower (HP / kW)	6.0 / 4.4
Fuel Capacity (US Gal / L)	0.5 / 2.0
Pump	Giant Axial
Operating Pressure (PSI / Bar)	2700 / 186
Volume (US GPM / Litres)	2.5 / 9.5
Pressure Hose (Ft. / m)	50 / 15
Dimensions (in / cm)	38 x 21 x 33 / 92 x 51 x 80
Net Weight (lb. / kg)	89 / 41



2500 PSI, 3.0 GPM

- 🔥 Honda 6.5 HP GX Series OHV engine
- 🔥 Triplex pump with ceramic plungers
- 🔥 Forged brass manifold with variable pressure
- 🔥 Maximum pump operating temperature of 70° C / 160° F
- 🔥 Chemical injector with soap metering valve
- 🔥 Powder coated frame with removable handle
- 🔥 Thermal relief valve
- 🔥 10 inch pneumatic wheels
- 🔥 36 inch gun and wand assembly
- 🔥 Non-marking high pressure hose
- 🔥 Nozzle orifice size - 3.5
- 🔥 4 Quick coupled nozzles:
5° (yellow), 25° (green), 40° (white) and 50°
(black soap tip)
- 🔥 Pump Warranty: 5 Year Limited
(Excluding Wear Items)
- 🔥 Engine Warranty: 2 Years

Options

- 🔥 Hose Reel with 50 foot hose (see below)

HGP253E



HGP253E

▼ HGP253E

General Pump - 2500 PSI, 3.0 GPM, Two handle
"E" frame, 25 foot hose

Specifications

Power	Honda
Horsepower (HP / kW)	6.5 / 4.7
Fuel Capacity (US Gal / L)	.95 / 3.6
Pump	General
Operating Pressure (PSI / Bar)	2500 / 172
Volume (US GPM / Litres)	3.0 / 11.4
Pressure Hose (Ft. / m) – E	25 / 7
Pressure Hose (Ft. / m) – EH5	50 / 15
Dimensions (in / cm)	36 x 21 x 33 / 87 x 51 x 80
Net Weight (lb. / kg) – E	89 / 41
Net Weight (lb. / kg) – EH5	111 / 50



Shown with optional
Hose Reel HGP253EH5

GAS PRESSURE WASHERS

Industrial

2700 PSI, 3.0 GPM

- 🔥 Honda 6.5 HP GX Series OHV engine
- 🔥 Triplex pump with ceramic plungers
- 🔥 Forged brass manifold with variable pressure
- 🔥 Maximum pump operating temperature of 70° C / 160° F
- 🔥 Chemical injector with soap metering valve
- 🔥 Powder coated frame with removable handle
- 🔥 Thermal relief valve
- 🔥 10 inch pneumatic wheels
- 🔥 36 inch gun and wand assembly
- 🔥 Non-marking high pressure hose
- 🔥 Nozzle orifice size - 3.5
- 🔥 4 Quick coupled nozzles:
5° (yellow), 25° (green), 40° (white) and 50° (black soap tip)
- 🔥 Pump Warranty: 5 Year Limited
(Excluding Wear Items)
- 🔥 Engine Warranty: 2 Years

Options

- 🔥 Hose Reel with 50 foot hose (see below)



HC273E

▼ HC273E

Cat Pump - 2700 PSI, 3.0 GPM, Two handle
"E" frame, 25 foot hose

Specifications

Power	Honda
Horsepower (HP / kW)	6.5 / 4.7
Fuel Capacity (US Gal / L)	.95 / 3.6
Pump	Cat
Operating Pressure (PSI / Bar)	2700 / 186
Volume (US GPM / Litres)	3.0 / 11.4
Pressure Hose (Ft. / m) – E	25 / 7
Pressure Hose (Ft. / m) – EH5	50 / 15
Dimensions (in / cm)	36 x 21 x 33 / 87 x 51 x 80
Net Weight (lb. / kg) – E	89 / 41
Net Weight (lb. / kg) – EH5	111 / 50



Shown with optional
Hose Reel HC273EH5

3500 PSI, 4.0 GPM

- 🔥 Honda 13 HP GX Series OHV engine with low oil shut down
- 🔥 Triplex pump with ceramic plungers
- 🔥 Forged brass manifold with variable pressure
- 🔥 Maximum pump operating temperature of 70° C / 160° F
- 🔥 Chemical injector with soap metering valve
- 🔥 Thermal relief valve
- 🔥 Powder coated frame with removable handle
- 🔥 13 inch pneumatic wheels
- 🔥 36 inch gun and wand assembly
- 🔥 Non-marking high pressure hose
- 🔥 Nozzle orifice size - 4.0
- 🔥 4 Quick coupled nozzles:
15° (yellow), 25° (green), 40° (white) and 50° (black soap tip)
- 🔥 Pump Warranty: 5 Year Limited
(Excluding Wear Items)
- 🔥 Engine Warranty: 2 Years

Options

- 🔥 Electric start
- 🔥 Hose Reel with 50 foot hose (see below)

HGP354C



HGP354C

▼ HGP354C

General Pump - 3500 PSI, 4.0 GPM, Two handle
"C" frame, 50 foot hose

Specifications

Power	Honda
Horsepower (HP / kW)	13 / 9.6
Fuel Capacity (US Gal / L)	1.7 / 6.5
Pump	General
Operating Pressure (PSI / Bar)	3500 / 241
Volume (US GPM / Litres)	4.0 / 15.1
Pressure Hose (Ft. / m)	50 / 15
Dimensions (in / cm)	38 x 23 x 37 / 92 x 56 x 90
Net Weight (lb. / kg) – C	145 / 66
Net Weight (lb. / kg) – CH	168 / 76



Shown with optional
Hose Reel
HGP354CH

GAS PRESSURE WASHERS

Industrial

4000 PSI, 4.0 GPM

- 🔥 Honda 13 HP GX Series OHV engine with low oil shut down
- 🔥 Triplex pump with ceramic plungers
- 🔥 Forged brass manifold with variable pressure
- 🔥 Maximum pump operating temperature of 70° C / 160° F
- 🔥 Chemical injector with soap metering valve
- 🔥 Thermal relief valve
- 🔥 Powder coated frame with removable handle
- 🔥 13 inch pneumatic wheels
- 🔥 36 inch gun and wand assembly
- 🔥 Non-marking high pressure hose
- 🔥 Nozzle orifice size - 3.5
- 🔥 4 Quick coupled nozzles:
15° (yellow), 25° (green), 40° (white) and
50° (black soap tip)
- 🔥 Pump Warranty: 5 Year Limited
(Excluding Wear Items)
- 🔥 Engine Warranty: 2 Years

Options

- 🔥 Electric start



▼ HC404C

Cat Pump - 4000 PSI, 4.0 GPM, Two handle
"C" frame, 50 foot hose

Specifications

Power	Honda
Horsepower (HP / kW)	13 / 9.6
Fuel Capacity (US Gal / L)	1.7 / 6.5
Pump	Cat
Operating Pressure (PSI / Bar)	4000 / 276
Volume (US GPM / Litres)	4.0 / 15.1
Pressure Hose (Ft. / m)	50 / 15
Dimensions (in / cm)	38 x 23 x 37 / 92 x 56 x 90
Net Weight (lb. / kg)	145 / 66



2500 PSI, 5.6 GPM

- 🔥 Honda 13HP GX Series OHV engine with electric start
- 🔥 Triplex pump with ceramic plungers and gear box
- 🔥 Roll cage frame
- 🔥 Stainless fittings
- 🔥 Hose reel with 50 foot hose
- 🔥 Soap Tank 10L
- 🔥 12V battery
- 🔥 10" pneumatic wheels
- 🔥 36 inch gun and wand assembly
- 🔥 Nozzle orifice size - 9.0
- 🔥 4 Quick coupled nozzles:
15° (yellow), 25° (green), 40° (white)
and 50° (black soap tip)
- 🔥 Pump Warranty: 5 Year Limited
(Excluding Wear Items)
- 🔥 Engine Warranty: 2 Years

Options

- 🔥 Dual hose reel and wand splitter for multi gun operation , Pulsation dampener, Ball valve - use model HGP255LHHE

HGP255LHE



HGP255LHE

▼ HGP255LHE

General Pump - 2500 PSI, 5.6 GPM, Roll Cage
"L" frame, 50 foot hose

Specifications

Power	Honda
Horsepower (HP / kW)	13 / 9.6
Fuel Capacity (US Gal / L)	1.7 / 6.5
Pump	General
Operating Pressure (PSI / Bar)	2500 / 172
Volume (US GPM / Litres)	5.6 / 21.2
Pressure Hose (Ft. / m)	50 / 15
Dimensions (in / cm)	36 x 26 x 26.5
Net Weight (lb. / kg)	170 / 77



Shown with optional
Dual Hose Reel
HGP255LHHE

GAS PRESSURE WASHERS

Factory Options

Model	Digital Tach	Electric Start	Hose Reel	Throttle Control Valve
HG202B	960000	—	—	—
HG272EH5	960000	—	Standard	—
HGP253E	960000	—	UGREEL	UGTCV
HC273E	960000	—	UGREEL	UGTCV
HGP354C	960000	UGESTRT	UGREEL	UGTCV
HC404C	960000	UGESTRT	—	UGTCV
HGP255LHE	960000	Standard	Standard	—
HGP255LHHE	960000	Standard	Standard	—




960000



UGESTRT



UGREEL



UGTCV



Factory
Options

Warranty

STORM Pressure Washers will repair or replace, free of charge, any part or parts that are defective in material or workmanship. Transportation on parts or equipment submitted for repair or replacement under this warranty remains the responsibility of the purchaser. This warranty is effective for the time periods and subject to the conditions provided for in this policy. Warranty work must be performed by an authorized STORM Pressure Washers Warranty Depot. For details on warranty locations, contact STORM Pressure Washers at 1 (800) 882-1961. STORM reserves the right to refuse any claim do to negligence or abuse.

Warranty Period

Warranty coverage commences on the date of purchase by the end user or on the date the product has been first used for demonstration purposes.

Parts and Accessories:	90 Days - excluding wear items
Machines: Consumer Duty	1 year - excluding wear items
Machines: Light Industrial	2 years - excluding wear items
Machines: Industrial: Engines	2 years – excluding wear items
Machines: Industrial: Pumps	5 years – excluding wear items

Disclaimer

Items not covered under warranty include normal wear & tear items such as O-rings, V-sleeves and packings, hose outer protective jacket, unloaders and spray nozzles.

STORM Pressure Washers shall not be liable for loss of time or use of the product, or any other indirect, incidental or consequential damages, inconvenience or commercial loss.

Customer Responsibility

Customer must complete and submit warranty registration form online for each new machine within 90 days of purchase date.

Proper service must be performed as detailed in the owner's manual. NOTE: Use only STORM approved pump oil, as indicated in the owner's manual.

Modifications and after market parts or accessories may void overall warranty coverage.

Repairs required as a result of collision, accident, negligence, misuse and lack of maintenance are not covered under warranty.

Repair work, including disassembly inspections, must be performed by an authorized STORM Pressure Washers Depot.

Customer must provide the means of delivering the product to and from the STORM Pressure Washers Warranty Depot. (Freight is not an expense covered under warranty). For the nearest STORM Pressure Washers Warranty Depot, please call STORM Pressure Washers toll free at 1 (800) 882-1961.



Warranty